

Skid Steer Features and Specifications

10/28/2006



**SK-600 SS
SC721818**

**SK-650 SS
SC781818**

**SK-700 SS
SC841818**

Features

Grading and Leveling	Fine Swale, Precision Grading and Leveling	Fine Swale, Precision Grading and Leveling	Fine Swale, Precision Grading and Leveling
Blade Angle	0 – 30 Degree	0 – 30 Degree	0 - 30 Degree
Frame and Box Design	Tubular Steel Frame Gusset Reinforced	Tubular Steel Frame Gusset Reinforced	Tubular Steel Frame Gusset Reinforced
Cutting Edges	Reversible	Reversible	Reversible
Compatibility	15 ° Skid Steer Backing Plate	15 ° Skid Steer Backing Plate	15 ° Skid Steer Backing Plate
Scarifier Shank	3 Position	3 Position	3 Position
Center Shield	Full Coverage	Full Coverage	Full Coverage

Specifications

Capacity	13.5 Cu. Ft.	14.6 Cu. Ft.	15.75 Cu. Ft.
Cutting Edge	(2) 5/8" x 6" Case Hardened	(2) 5/8" x 6" Case Hardened	(2) 5/8" x 6" Case Hardened
Skid Steer HP	27 – 45 HP	27 – 85 HP	40 – 85 HP
Working Width	72"	78"	84"
Moldboard Height	18"	18"	18"
Moldboard Thickness	¼" + ¼" Curved	¼" + ¼" Curved	¼" + ¼" Curved
Duty	Heavy	Heavy	Heavy
Side Wing	18"	18"	18"
Scarifier Shank	(1) Replaceable	(1) Replaceable	(1) Replaceable
Assembly Required	Hydraulics Only	Hydraulics Only	Hydraulics Only

Operating Weight	772 lbs	827 lbs	882 lbs
Shipping Weight	822 lbs	877 lbs	932 lbs
Packaging	1 Pallet	1 Pallet	1 Pallet
Shipping Dimensions	30" H x 73" W x 43"D	30" H x 79" W x 43"D	30" H x 85" W x 43"D

Warranty	1 Year Warranty	1 Year Warranty	1 Year Warranty
-----------------	-----------------	-----------------	-----------------